

SPECIFICATION SHEET

Triple Unit Lockdown Frame



3 x 2 (ft) Slab 2200 x 990
2 x 2 (ft) Slab 2200 x 690

Height 1435mm
Capacity 3 x 120L / 240L
360L

TECHNICAL DETAILS

Manufactured from:

- 50mm O.D Mild Steel Tube 1.5 ERW.
- 25mm O.D Mild Steel Tube 1.2 ERW.
- 3/4" O.D Stainless Steel Tube 1.5 304 grade.
- 3/4" SH5 Stainless Steel Tube 1.5 304 grade.
- 31.75mm O.D Stainless Steel Tube 1.5 304 grade.
- 2mm Zintec, BS EN 10152: 1994 DC+ZE25 / 25-AC.
- 1.5mm Zintec, BS EN 10152: 1994 DC+ZE25 / 25-AC.
- 1.2mm Zintec, BS EN 10152: 1994 DC+ZE25 / 25-AC.
- 40 x 6 Stainless Steel Flat Bar.
- 50 x 6 Mild Steel Flat Bar.
- 40 x 40 x 2.5mm Mild Steel Box Section.
- 50 x 50 x 5mm Mild Steel Angle Iron.
- 6mm Stainless Steel Wire.

Pre-treatment:

- 3 stage degreasing process incorporating an iron phosphate coating and a non chrome final rinse enhancing the anti-corrosive properties of the metal and ensuring a high quality bonding of paint to metal.

Paint Finish:

- Polyester powder finish to customer specification.

FEATURES - STANDARD

- Large area for provision of signage.
- Can accommodate for 3 x 120 / 240 / 360L wheeled bins.
- Wheeled bins locked at front keeping handles free.
- Manufactured in Mild Steel and Stainless Steel used in high wearing parts.
- 2 x 2 / 3 x 2 concrete flag options available.
- Delivered in flat pack for self assembly.
- Fixing bolts provided.
- Concrete slabs reduce the need to fix unit in place if required.
- Fixing holes provided to secure to ground if required.
- Stainless Steel locking bar assembly.
- Slam Lock mechanism.
- Adjustable 'Lid Stop' & Lock Bar provides flexibility for use with different types of bin.

FEATURES - OPTIONAL

- Key Lock available.
- Stainless Steel option for improved durability.
- Bins can be positioned back first to allow partial opening of lid.
- Concrete slabs available.
- Bins can be provided with apertures.